

Shelflife & storage requirements

Zitrec® EC 30 can be stored for minimum 3 years in unopened containers without any effect on the product quality or performance. The product should be stored above -14°C for the 25% EG version and above -45°C for the 54% EG version. Periods of exposure to temperatures above 35°C should be minimised.

It is strongly advised not to expose the fluid in translucent packages to direct sunlight because this can result in fading of the colour or discoloration over time. This reaction can be accelerated if coupled with high ambient temperatures.

It is therefore advisable to store the fluid indoors, to use new and not recycled containers and where possible packages with a UV filter. As with any heat transfer fluid, the use of galvanised steel is not recommended for pipes or any other part of the storage/mixing installation and for packaging.

Compatibility and mixability

Zitrec® EC 30 is compatible with most other heat transfer fluids based on glycol and water. Exclusive use of **Zitrec® EC 30** is however recommended for optimum performance.

DRAFT

The information contained in this Product Information Leaflet is intended to provide the customer and/or end-user with an understanding of the properties of the product, it being understood that this information may not be construed as any express or implied warranty that the product is suitable for a specific use or application.

All information contained in this Product Information Leaflet, including but not limited to text or graphic material, is the property of Artec NV, is accurate to the best of our knowledge at the date of issue specified, supersedes all previous editions and information contained in them, and is subject to change without notice.

Any textual or graphic material you copy, print, or download from this Product Information Leaflet is for your personal, non-commercial use only, and you not change or delete any copyright, trademark or other proprietary notices. Any other use, including but not limited to the reproduction, distribution, display or transmission of the content of this document is strictly prohibited, unless authorized by Artec NV in writing.

Version 202501-v01.1